

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 March 2003 (20.03.2003)


PCT

(10) International Publication Number
WO 03/022417 A2

- (51) International Patent Classification⁷: **B01J**
- (21) International Application Number: PCT/US02/21860
- (22) International Filing Date: 26 June 2002 (26.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/301,493 27 June 2001 (27.06.2001) US
- (71) Applicant (for all designated States except US): **NU ELEMENT, INC.** [US/US]; 6401 1st Street N.E., Tacoma, WA 98422 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DAVIS, Eric, J.** [US]; 110 N.W. 74th Street, Seattle, WA 98117 (US). **BOWEN, Ray, J.** [US]; 5324 N.E. 86th Street, Seattle, WA 98115 (US). **PEDERSEN, Jeffrey, M.** [US]; 3835 South "A" Street, Tacoma, WA 98408 (US). **FLECKNER, Karen** [US]; 1922 Lighthouse Lane N.E., Tacoma, WA 98422 (US).
- (74) Agents: **RICKARDS, Glenn, P.** et al.; Dorsey & Whitney LLP, Suite 3400, 1420 Fifth Avenue, Seattle, WA 98101 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: MODULAR MICRO-REACTOR ARCHITECTURE AND METHOD FOR FLUID PROCESSING DEVICES



(57) Abstract: A modular fluid processing architecture is provided that consists of a matrix of nested tubes secured between end block manifolds. Multiple chemical reactors may be housed in the annular spaces formed by the nesting of the tubes, and the processes may be integrated through flow splitting, mixing, switching and heat exchange in the manifolds. A flow switching system may provide the ability to switch the flows on or off in individual processors or in banks of such processors. The switching may effect the operation of some or all of the processes. Such switching can facilitate rapid and close following of demand for the processor output while allowing each processor to run within a range of high efficiency, since processors may be turned off or on in response to falling or rising demand for the output.



WO 03/022417 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.